




Electrically isolated base plate
 Industrial standard package
 Simplified mechanical design, rapid assembly
 Pressure contact

**Double Diode Module
 For Phase Control
 MDx-400-52-A2**

Average forward current			I_{FAV}	400 A
Repetitive peak reverse voltage			V_{RRM}	4600 ÷ 5200 V
V_{RRM}, V	4600	4800	5000	5200
Voltage code	46	48	50	52
$T_j, °C$	- 40 ÷ 140			




All dimensions in millimeters (inches)

MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions
ON-STATE				
I_{FAV}	Average forward current	A	400	$T_c=97\text{ }^\circ\text{C}$; 180° half-sine wave; 50 Hz
I_{FRMS}	RMS forward current	A	628	
I_{FSM}	Surge forward current	kA	8.0 9.0	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p=10\text{ ms}$; single pulse; $V_R=0\text{ V}$;
			8.5 10.0	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p=8.3\text{ ms}$; single pulse; $V_R=0\text{ V}$;
I^2t	Safety factor	$A^2s\cdot 10^3$	320 400	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p=10\text{ ms}$; single pulse; $V_R=0\text{ V}$;
			290 410	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p=8.3\text{ ms}$; single pulse; $V_R=0\text{ V}$;
BLOCKING				
V_{RRM}	Repetitive peak reverse voltages	V	4600÷5200	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$; 180° half-sine wave; 50 Hz;
V_{RSM}	Non-repetitive peak reverse voltages	V	4700÷5300	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$; 180° half-sine wave; single pulse;
V_R	Reverse continuous voltages	V	$0.6\cdot V_{RRM}$	$T_j=T_{j\text{ max}}$;
THERMAL				
T_{stg}	Storage temperature	$^\circ\text{C}$	-40 ÷ 50	
T_j	Operating junction temperature	$^\circ\text{C}$	-40 ÷ 140	
$T_{c\text{ op}}$	Operating temperature	$^\circ\text{C}$	-40 ÷ 125	
MECHANICAL				
a	Acceleration under vibration	m/s^2	50	

CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
ON-STATE					
V_{FM}	Peak forward voltage, max	V	2.40	$T_j=25\text{ }^\circ\text{C}$; $I_{FM}=1570\text{ A}$	
$V_{F(TO)}$	Forward threshold voltage, max	V	0.80	$T_j=T_{j\text{ max}}$;	
r_T	Forward slope resistance, max	$m\Omega$	0.800	$0.5\pi I_{FAV} < I_T < 1.5\pi I_{FAV}$	
BLOCKING					
I_{RRM}	Repetitive peak reverse current, max	mA	100	$T_j=T_{j\text{ max}}$; $V_R=V_{RRM}$	
THERMAL					
R_{thjc}	Thermal resistance, junction to case			180° half-sine wave, 50 Hz	
	per module	$^\circ\text{C/W}$	0.0340		
	per arm	$^\circ\text{C/W}$	0.0680		
	per module	$^\circ\text{C/W}$	0.0325	DC	
per arm	$^\circ\text{C/W}$	0.0650			
R_{thch}	Thermal resistance, case to heatsink				
	per module	$^\circ\text{C/W}$	0.0100		
	per arm	$^\circ\text{C/W}$	0.0200		
INSULATION					
V_{ISOL}	Insulation test voltage	kV	3.00	Sine wave, 50 Hz; RMS	$t=60\text{ sec}$
			3.60		$t=1\text{ sec}$
MECHANICAL					
M_1	Mounting torque (M6) ¹⁾	Nm	6.00	Tolerance $\pm 15\%$	
M_2	Terminal connection torque (M10) ¹⁾	Nm	12.00	Tolerance $\pm 15\%$	
w	Weight, max	g	1500		

PART NUMBERING GUIDE						NOTES					
MD	3	-	400	-	52	-	A2	-	N		1) The screws must be lubricated
1	2		3		4		5		6		
1. MD - Rectifier Diode 2. Circuit Schematic: 3 – serial connection 4 – common Cathode 5 – common Anode 3. Average Forward Current, A 4. Voltage Code 5. Package Type (M.A2) 6. Ambient Conditions: N – Normal											
		UL certified file-No. E255404									

The information contained herein is confidential and protected by Copyright
In the interest of product improvement, Proton-Electrotex reserves the right to change data sheet without notice.