High power cycling capability
Low on-state and switching losses
Optimized for line frequency rectifiers
Designed for traction and industrial applications

Power Rectifier Avalanche Diodes
Type DA243-500-28

Average forward current		I_{FAV}	500 A		
Repetitive peak reverse voltage		V_{RRM}	2000 ÷ 2800 V		
V_{RRM}, V	2000	2200	2400	2600	2800
Voltage code	20	22	24	26	28
T_j, °C	– 60 ÷ 150				

MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions	
ON-STATE					
I_{FAV}	Average forward current	A	500 670	T_c=120 °C; Double side cooled; T_c=100 °C; Double side cooled; 180° half-sine wave; 50 Hz	
I_{FRMS}	RMS forward current	A	785	T_c=120 °C; Double side cooled; 180° half-sine wave; 50 Hz	
I_{FSM}	Surge forward current	kA	13.0 15.0	T_j=$T_{j\,max}$ T_j=25 °C	180° half-sine wave; t_p=10 ms; single pulse; V_R=0 V;
			14.0 16.0	T_j=$T_{j\,max}$ T_j=25 °C	180° half-sine wave; t_p=8.3 ms; single pulse; V_R=0 V;
I^2t	Safety factor	$A^2s\cdot10^3$	845 1125	T_j=$T_{j\,max}$ T_j=25 °C	180° half-sine wave; t_p=10 ms; single pulse; V_R=0 V;
			810 1060	T_j=$T_{j\,max}$ T_j=25 °C	180° half-sine wave; t_p=8.3 ms; single pulse; V_R=0 V;
BLOCKING					
V_{RRM}	Repetitive peak reverse voltages	V	2000÷2800	$T_{j\,min}$< T_j <$T_{j\,max}$; 180° half-sine wave; 50 Hz;	
$V_{(BR)}$	Breakdown voltage	V	2450÷3250	T_j=25 °C; I_{br}=100 mA; t_p = 10 ms; 5 Hz	
V_R	Reverse continuous voltages	V	0.75·V_{RRM}	T_j=$T_{j\,max}$;	
P_{RSM}	Surge reverse power dissipation	kW	16	T_j= $T_{j\,max}$; t_p = 100 µs; 180° half-sine current waveforms; single pulse	
THERMAL					
T_{stg}	Storage temperature	°C	– 60 ÷ 50		
T_j	Operating junction temperature	°C	– 60 ÷ 150		
MECHANICAL					
F	Mounting force	kN	14.0 ÷ 16.0		
a	Acceleration	m/s^2	50 100	Device unclamped Device clamped	

CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
ON-STATE					
V_{FM}	Peak forward voltage, max	V	2.00	T_j=25 °C; I_{FM}=1570A	
$V_{F(TO)}$	Forward threshold voltage, max	V	1.00	$T_j=T_{j\,max}$; 0.5 π I_{FAV} < I_T < 1.5 π I_{FAV}	
r_T	Forward slope resistance, max	mΩ	0.800		
BLOCKING					
I_{RRM}	Repetitive peak reverse current, max	mA	70	$T_j=T_{j\,max}$; $V_R=V_{RRM}$	
THERMAL					
R_{thjc}	Thermal resistance, junction to case, max	°C/W	0.0300	Direct current	Double side cooled
R_{thjc-A}			0.0704		Anode side cooled
R_{thjc-K}			0.0576		Cathode side cooled
R_{thck}	Thermal resistance, case to heatsink, max	°C/W	0.0060	Direct current	
MECHANICAL					
w	Weight, typ	g	260		
D_s	Surface creepage distance	mm (inch)	23.69 (0.933)		
D_a	Air strike distance	mm (inch)	19.10 (0.752)		

PART NUMBERING GUIDE

DA	243	500	28	N
1	2	3	4	5

1. DA — Avalanche Diode
2. Design version
3. Average forward current, A
4. Voltage code
5. Ambient conditions: N – normal; T – tropical

OVERALL DIMENSIONS

Package type: D.C2



All dimensions in millimeters (inches)

The information contained herein is confidential and protected by Copyright.
In the interest of product improvement, Proton-Electrotex reserves the right to change data sheet without notice.