MBM450FS33F

Silicon N-channel IGBT 3300V F version



Circuit diagram

FEATURES

- High current density package
- Low stray inductance & low Rth(j-c)
- Half-bridge (2in1)
- Built in temperature sensor
- Scalable large current easily handled by paralleling
- Equipped with current sensing terminals

ABSOLUTE MAXIMUM RATINGS (Tc=25°C)

Item		Symbol	Unit	MBM450FS33F
Collector Emitter Voltage		V_{CES}	V	3,300
Gate Emitter Voltage		V_{GES}	V	±20
Collector Current	DC	I_C	A	450
	1ms	I_{CM}		900
Forward Current	DC	I_F	A	450
	1ms	I_{FM}		900
Junction Temperature		$T_{vj\ op}$	°C	-50 ~ +150
Storage Temperature		T_{stg}	°C	-55 ~ +150
Isolation Voltage		V_{ISO}	V_{RMS}	6,000(AC 1 minute)
Screw Torque	Terminals (M3/M8)	M	N·m	0.8/15
	Mounting (M6)	M		6.0 (1)

Notes: (1) Recommended Value 5.5±0.5N·m

ELECTRICAL CHARACTERISTICS

Item		Symbol	Unit	Min.	Typ.	Max.	Test Conditions
Collector Emitter Cut-Off Current		I_{CES}	mA	-	-	0.30	V_{CE}=3,300V, V_{GE}=0V, T_{vj}=25°C
				-	15	50	V_{CE}=3,300V, V_{GE}=0V, T_{vj}=150°C
Gate Emitter Leakage Current		I_{GES}	nA	-500	-	+500	V_{GE}=±20V, V_{CE}=0V, T_{vj}=25°C
Collector Emitter Saturation Voltage		V_{CEsat}	V	-	2.25	-	I_C=450A, V_{GE}=15V, T_{vj}=25°C
				2.50	3.05	3.50	I_C=450A, V_{GE}=15V, T_{vj}=150°C
Gate Emitter Threshold Voltage		$V_{GE(th)}$	V	5.5	6.5	7.5	V_{CE}=10V, I_C=450mA, T_{vj}=25°C
Input Capacitance		C_{ies}	nF	-	24	-	V_{CE}=10V, V_{GE}=0V, f=100kHz, T_{vj}=25°C
Internal Gate Resistance		$R_{g(int)}$	Ω	-	6.2	-	V_{CE}=10V, V_{GE}=0V, f=100kHz, T_{vj}=25°C
Switching Times	Rise Time	t_r	μs	-	0.12	-	V_{CC}=1800V, I_C=450A
	Turn On Time	t_{on}		-	0.60	-	Ls=40nH
	Fall Time	t_f		-	1.30	-	R_G(on/off)=6.8Ω/12Ω (2)
	Turn Off Time	t_{off}		-	2.40	-	V_{GE}=±15V, T_{vj}=150°C
Forward Voltage Drop		V_F	V	-	2.25	-	I_F=450A, V_{GE}=0V, T_{vj}=25°C
				2.10	2.45	2.80	I_F=450A, V_{GE}=0V, T_{vj}=150°C
Reverse Recovery Time		t_{rr}	μs	-	1.10	-	V_{CC}=1800V, I_F=450A, Ls =40nH T_{vj}=150°C
Turn-on Loss per Pulse		E_{on}	J/P	-	0.73	-	V_{CC}=1800V, Ic=450A, Ls =40nH
Turn-off Loss per Pulse		E_{off}	J/P	-	0.63	-	R_G(on/off)=6.8Ω/12Ω (2)
Reverse Recovery Loss per Pulse		E_{rr}	J/P	-	0.68	-	V_{GE}=±15V, T_{vj}=150°C
Short Circuit Pulse Width		tsc	μs	10	-	-	Vcc=2200V,Ls=40nH R_G(on/off)=6.8/68Ω,V_{GE}=±15V,Tc=150℃
Stray Inductance Module		L_{SCE}	nH	-	9	-	Between C1(main) and E2(main)
NTC-Thermistor	Resistance	R_{25}	kΩ	-	5	-	Tc=25°C
	Deviation	ΔR/R	%	-5		5	Tc=25°C
	B-constant	$B_{(25/50)}$	K	-	3375	-	Between 25℃ and 50℃
Thermal Impedance	IGBT	Rth(j-c)	K/W	-	-	0.035	Junction to case
	FWD	Rth(j-c)		-	-	0.055	
Contact Thermal Impedance		Rth(c-f)	K/W	-	0.02	-	Case to fin (per 1 arm)

Notes: (2) R_G value is a test condition value for evaluation, not recommended value.
Please determine the suitable R_G value by measuring switching behavior and checking results with the respective SOA.

* Please contact our representatives at order.
* For improvement, specifications are subject to change without notice.
* For actual application, please confirm this spec sheet is the newest revision.
* ELECTRICAL CHARACTERISTIC values according to IEC 60747–2 IEC 60747–9

HITACHI
Inspire the Next

MBM450FS33F

OUTLINE DRAWING

Unit in mm



Weight: 770(g)

HITACHI
Inspire the Next

MBM450FS33F



Collector Current vs. Collector to Emitter Voltage



Collector Current vs. Collector to Emitter Voltage



Forward Voltage of free-wheeling diode



QG-VGE curve

MBM450FS33F



Turn-on Loss vs. Collector Current



Turn-off Loss vs.Collector Current



Recovery Loss vs. Forward Current



Switching time vs. Collector Current

HITACHI
Inspire the Next

MBM450FS33F



Turn-on Loss vs. Gate Resistance



Turn-off Loss vs. Gate Resistance



Recovery Loss vs. Gate Resistance



Switching time vs. Gate Resistance

MBM450FS33F

RBSOA





Definition of RBSOA waveform

Reverse bias safe operation area (RBSOA)

Reverse Recovery SOA

Conditions:
Ls≤40nH, Vcc≤2200V, IF≤900A, di/dt≤2500A/us, Tj=150°C





$di/dt = \frac{0.5Irm}{\Delta t}$

Definition of Recovery di/dt

Reverse Recovery SOA

MBM450FS33F



Σ rth[n]*(1-exp(-t/τth[n]))

n	1	2	3	4	Unit
τ th[n]	1.80E-01	2.04E-02	7.46E-04	3.06E-03	sec
rth[n,IGBT]	2.52E-02	4.70E-03	7.66E-04	4.36E-03	K/W
rth[n,Diode]	3.70E-02	1.02E-02	9.42E-04	6.76E-03	K/W

Transient Thermal Impedance Curve



Thermistor Resistance vs. Temperature



Capacitance vs. Collector to Emitter Voltage

MBM450FS33F

HITACHI POWER SEMICONDUCTORS

Notices

1. The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact Hitachi sales department for the latest version of this data sheets.
2. Please be sure to read "Precautions for Safe Use and Notices" in the individual brochure before use.
3. In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, life-support-related medical equipment, fuel control equipment and various kinds of safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement. Or consult Hitachi's sales department staff.
4. In no event shall Hitachi be liable for any damages that may result from an accident or any other cause during operation of the user's units according to this data sheets. Hitachi assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in this data sheets.
5. In no event shall Hitachi be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
6. No license is granted by this data sheets under any patents or other rights of any third party or Hitachi Power Semiconductor Device, Ltd.
7. This data sheets may not be reproduced or duplicated, in any form, in whole or in part, without the expressed written permission of Hitachi Power Semiconductor Device, Ltd.
8. The products (technologies) described in this data sheets are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety not are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.

■ For inquiries relating to the products, please contact nearest overseas representatives that is located "Inquiry" portion on the top page of a home page.

Hitachi power semiconductor home page address http://www.hitachi-power-semiconductor-device.co.jp/en/